Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-830-4917

0.609 inches Overall Width: 0.438 inches Body Length: 5.094 inches Unthreaded Mounting Hole Diameter: 0.144 inches Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Bemovability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Nating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
0.438 inches Body Length: 5.094 inches Unthreaded Mounting Hole Diameter: 0.144 inches Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Body Length:         5.094 inches         Unthreaded Mounting Hole Diameter:         0.144 inches         Distance Between Mounting Facility Centers:         4.688 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         7.5 single mating end single contact grouping         Polarization Method:         Mating end         Shell Type:         Solid         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Gold single mating end single contact grouping
5.094 inches Unthreaded Mounting Hole Diameter: 0.144 inches Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Gold single mating end single contact grouping
Unthreaded Mounting Hole Diameter: 0.144 inches Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
0.144 inches Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Nating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Distance Between Mounting Facility Centers: 4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Gold single mating end single contact grouping
4.688 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         7.5 single mating end single contact grouping         Polarization Method:         Mating end         Shell Type:         Solid         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping
1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         7.5 single mating end single contact grouping         Polarization Method:         Mating end         Shell Type:         Solid         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Golper alloy single mating end single contact grouping         Locattor:         Gold single mating end single contact grouping
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingGold single mating end single contact groupingLocation:SolidMaterial:Contact Material:Contact Surface Treatment:Gold single mating end single contact groupingContact Surface Treatment:Solid Single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
7.5 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Polarization Method:Mating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact groupingInsert Material:
Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Shell Type:         Solid         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping         Insert Material:
Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping         Insert Material:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Gold single mating end single contact grouping Insert Material:
Insert Material:
Direction dially duration being the section of and
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold



**Precious Material And Weight:** 

0.023 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.