

View Online at <https://aerobasegroup.com/nsn/5935-00-831-8696>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

1.893 inches

Overall Diameter:

1.281 inches

Environmental Protection:

Corrosion resistant

Cable Entrance Diameter:

Between 0.490 inches and 0.510 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

16-23 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Rubber chloroprene class cr single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response

Included Contact Quantity:

22 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.023 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0