NSN 5935-00-832-4344

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-832-4344 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 1.156 inches **Bushing Diameter:** 0.500 inches **Overall Height:** 0.687 inches **Overall Width:** 0.687 inches **Environmental Protection:** Weatherproof **Unthreaded Mounting Hole Diameter:** 0.099 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Cable Entrance Diameter:** 0.219 inches **Distance From Mounting Shoulder To Front Face:** 0.550 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 10000.0 megahertz single mating end single contact grouping Shell Type: Solid

Connector Locking Method:

Bayonet pin

NSN 5935-00-832-4344

Electrical Receptacle Connector - Page 2 of 3



| On any and an Only I Official Publish Mother de |
|---|
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 56 |
| Thread Size: |
| 0.099 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| nsert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Gold and silver |
| ncluded Contact Quantity: |
| 1 single mating end single contact grouping |
| ncluded Contact Type: |
| Coaxial pin single mating end single contact grouping |
| Precious Material And Location: |
| Shell surface gold and shell surface silver |
| Precious Material And Weight: |
| 0.100 gold grains, troy and 0.100 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Test Data Document: |
| 31349-mil-c-3608 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Jnf |
| Specification Data: |
| 31349-mil-c-3608 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Fiig:

No

Demilitarization:

NSN 5935-00-832-4344

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-c-3608 spec.