## NSN 5935-00-832-4890

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-832-4890



**Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape **Overall Length:** 1.562 inches **Overall Height:** 0.781 inches **Overall Width:** 0.438 inches **Distance Between Mounting Facility Centers:** 1.250 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.266 inches Thready Qty Per Inch (tpi): 40 and 32 **Thread Size:** 0.112 inches and 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material: Plastic melamine

Plastic melamine single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-832-4890

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A039b0