Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-832-4893

New Online at https://aerobasegroup.com/nsi//3505-00-002-4095
Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape w/screw locks
Overall Length:
0.875 inches
Overall Height:
0.844 inches
Overall Width:
0.344 inches
Environmental Protection:
Fire resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
485.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.109 inches
Operating Tempurature Rating: 500.0 degrees fahrenheit
Features Provided:
Pre-tinned terminal
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Back single making end single contact grouping

NSN 5935-00-832-4893 Electrical Plug Connector - Page 2 of 2



Contact Materia	al:
Copper alloy sin	gle mating end single contact grouping
Contact Surface	e Treatment:
Gold single mati	ng end single contact grouping and silver single mating end single contact grouping
Insert Material:	
Plastic diallyl ph	thalate glass filled single mating end
Contact Surface	e Treatment Specification:
Mil-g-45204 milit	ary specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd
treatment respor	nse single mating end single contact grouping
Terminal Type:	
Solder well singl	e mating end single contact grouping
Insert Material	Specification:
Mil-p-19833, typ	e gdi-30f military specification single material response single mating end
Included Conta	ct Quantity:
11 single mating	end single contact grouping
Included Conta	ct Type:
Round socket sin	ngle mating end single contact grouping
Precious Mater	ial And Location:
Contact surfaces	s gold and contact surfaces silver
Precious Mater	ial And Weight:
0.011 gold grain	s, troy and 0.011 silver grains, troy
Precious Mater	ial:
Gold and silver	
Thread Series	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	e:
Demilitarization	
No	
Fiig:	
A039b0	
Mil-std (military	y Standard):
Mil-g-45204 spe	С.