## NSN 5935-00-832-8015

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-832-8015 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.984 inches **Overall Diameter:** 1.437 inches **Distance From Mounting Shoulder To Front Face:** 0.656 inches **Mounting Facility Thickness:** 0.094 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 27-13 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Spring friction **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Insert Material:** Rubber chloroprene class cr single mating end **Terminal Type:** Solder well single mating end all contact groupings

## NSN 5935-00-832-8015

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Included Contact Quantity:
3 single mating end 1st contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Round pin single mating end 2nd contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0