NSN 5935-00-832-9786

14 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-832-9786 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.230 inches and 1.270 inches **Overall Height:** Between 0.810 inches and 0.850 inches **Overall Width:** Between 0.420 inches and 0.460 inches **Distance Between Mounting Facility Centers:** Between 0.932 inches and 0.939 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw Thread Size: 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:**

NSN 5935-00-832-9786

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Slotted guide
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.014\ gold\ grains,\ troy\ and\ 0.014\ silver\ grains,\ troy$
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0