## NSN 5935-00-833-0256

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-833-0256

**Body Style:**Right angle type

**Overall Length:** 

Between 3.321 inches and 3.371 inches

**Overall Width:** 

Between 0.578 inches and 0.608 inches

**Body Height:** 

Between 0.610 inches and 0.672 inches

**Environmental Protection:** 

Vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

3.000 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

1 row of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-00-833-0256

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Polarized k contact removed
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030b0