Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-833-0260

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 2.714 inches and 2.724 inches
Overall Height:
Between 0.792 inches and 0.802 inches
Overall Width:
Between 1.229 inches and 1.239 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
75 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Jackscrew and guide pin/socket
Connector Locking Method:
Jackscrew-socket
Operating Tempurature Rating:
Between -55.0 degrees celsius and 95.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and silver single mating end single contact grouping

## **NSN 5935-00-833-0260** Electrical Plug Connector - Page 2 of 2



Insert Material:	
Plastic diallyl phthalate glass filled sing	gle mating end
Contact Surface Treatment Specifica	ation:
Mil-g-45204, type 1 military specification	on 1st treatment response and qq-s-365, type 1, grade b federal specification 2nd treatment respons
single mating end single contact group	ing
Terminal Type:	
Solder well single mating end single co	ontact grouping
Insert Material Specification:	
Mil-m-14, type gdi-30 military specifica	tion single material response single mating end
Included Contact Quantity:	
75 single mating end single contact gro	puping
Included Contact Type:	
Round pin single mating end single co	ntact grouping
Precious Material And Location:	
Contact surfaces gold and contact surf	faces silver
Precious Material And Weight:	
0.075 gold grains, troy and 0.075 silve	er grains, troy
Precious Material:	
Gold and silver	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	