NSN 5935-00-833-5719

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-833-5719

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 1.466 inches |
| Overall Diameter: |
| 1.158 inches |
| Mating End Quantity: |
| 2 |
| Contact Removability: |
| Nonremovable all mating ends single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 all mating ends single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin and bayonet latch |
| Contact Material: |
| Copper alloy all mating ends single contact grouping |
| Contact Surface Treatment: |
| Gold all mating ends single contact grouping |
| Insert Material: |
| Plastic epoxy all mating ends |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response all mating ends single contact grouping |
| Contact Material Specification: |
| Qq-c-530 temper h federal specification single material response all mating ends single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Material Specification: |
| Qq-a-200/8b t6 federal specification single material response or qq-a-250/11c federal specification single material response |
| Included Contact Quantity: |
| 19 all mating ends single contact grouping |
| Included Contact Type: |
| Round socket 2nd mating end single contact grouping |
| Precious Material And Location: |

Contact surfaces gold

NSN 5935-00-833-5719

Connector Adapter - Page 2 of 2



| Precious Material And Weight: |
|--------------------------------------|
| 0.038 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.