Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-833-6640

2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
6.219 inches
Overall Diameter:
3.031 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
135.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Basket weave grip
Thready Qty Per Inch (tpi):
4
Thread Size:
2.500 inches
Terminal Location:
Back single mating end single contact grouping

## **NSN 5935-00-833-6640** Electrical Plug Connector - Page 2 of 2



Conner allo	y single mating end single contact grouping
	irface Treatment:
	mating end single contact grouping
Insert Mate	
	one class q single mating end
	inface Treatment Specification:
	military specification single treatment response single mating end single contact grouping
Terminal T	
-	single mating end single contact grouping
Shell Mater	
Aluminum	ια
	ce Treatment:
Anodize	
	ontact Quantity:
	ting end single contact grouping
	ontact Type:
	et single mating end single contact grouping
Special Fea	
-	signation 20-36
	laterial And Location:
Contact sur	
	laterial And Weight:
0.025 gold g	
Precious M	
Gold	
Thread Ser	ies Designator:
Special acm	-
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	ation:
No	
Fiig:	
A039b0	
Mil-std (mil	litary Standard):
Mil-g-45204	spec.