Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-833-9943

| hread Class:   |  |
|--|--|
| a  |  |
| hread Direction:   |  |
| ight-hand  |  |
| ody Style:   |  |
| traight shape, flange mount, external coupling                             |  |
| verall Length:   |  |
| 812 inches   |  |
| verall Height:   |  |
| etween 1.719 inches and 1.781 inches                                       |  |
| verall Width:  |  |
| etween 1.719 inches and 1.781 inches                                       |  |
| nthreaded Mounting Hole Diameter:  |  |
| etween 0.142 inches and 0.152 inches                                       |  |
| enter To Center Distance Between Mounting Facilities Parallel To Height:   |  |
| etween 1.370 inches and 1.380 inches                                       |  |
| istance Between Centerlines Of Mounting Facilities Parallel To Body Width: |  |
| etween 1.370 inches and 1.380 inches                                       |  |
| able Entrance Diameter:  |  |
| 234 inches   |  |
| istance From Mounting Shoulder To Front Face:                              |  |
| etween 0.812 inches and 0.822 inches                                       |  |
| hreaded Device Type:   |  |
| oupling facility   |  |
| ating End Quantity:  |  |
|  |  |
| ontact Position Arrangement Style:   |  |
| 4-10 single mating end   |  |
| ontact Removability:   |  |
| onremovable single mating end single contact grouping                      |  |
| ontact Maximum Current Rating In Amps:                                     |  |
| 5.0 single mating end single contact grouping                              |  |
| ontact Maximum Ac Voltage Rating In Volts:                                 |  |
| 00.0 single mating end single contact grouping                             |  |
| ontact Maximum Dc Voltage Rating In Volts:                                 |  |
| 00.0 single mating end single contact grouping                             |  |
| olarization Method:  |  |
| eyway or multiple keyway   |  |
| sert Position In Deg:  |  |
| 0  |  |
| o<br>hell Type:  |  |
|  |  |



**Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Potting type **Thread Length:** 0.625 inches **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.007 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0