Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-834-0076

| Body Style: |
|---|
| Right angle type |
| Overall Length: |
| 1.560 inches |
| Overall Width: |
| 0.140 inches |
| Body Height: |
| 0.296 inches |
| Distance Between Mounting Facility Centers: |
| 1.360 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1 row of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Contact Material Specification: |
| Qq-b-750, comp a federal specification single material response single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 12 single mating end single contact grouping |
| Included Contact Type: |
| Hermaphrodite single mating end single contact grouping |
| |



Precious Material And Location: Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.