Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-834-2573

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.141 inches
Overall Diameter:
0.438 inches
Cable Entrance Diameter:
0.216 inches
Distance From Mounting Shoulder To Front Face: 0.500 inches
Mounting Facility Thickness:
0.125 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1 Contact Desition American Circles
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Frequency Rating:
500.0 megahertz single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



## **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold Shell Surface Treatment Specification: Mil-g-45204, type 2, class 1 military specification single treatment response **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Insert Material Specification:** Qq0b0626, comp 22 federal specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/double flat **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.