NSN 5935-00-834-3373

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-834-3373 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 2.067 inches **Overall Diameter:** 1.625 inches **Cable Entrance Diameter:** 0.940 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 35.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

Rubber synthetic single mating end

NSN 5935-00-834-3373Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0