# NSN 5935-00-834-5779

Anodize

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-834-5779

**Body Style:** Right angle type **Overall Length:** Between 3.321 inches and 3.371 inches Overall Width: Between 0.578 inches and 0.608 inches **Body Height:** Between 0.610 inches and 0.672 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 3.000 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

# NSN 5935-00-834-5779

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

#### **Insert Material Specification:**

Mil-m-14, type mdg military specification single material response single mating end

#### **Included Contact Quantity:**

14 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Polarized j contact removed

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.014 gold grains, troy and 0.014 silver grains, troy

#### **Precious Material:**

Gold and silver

### Shelf Life:

N/a

#### **Unit Of Measure:**

\_\_

#### **Demilitarization:**

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-m-14 spec.