

View Online at <https://aerobasegroup.com/nsn/5935-00-835-2680>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.563 inches

Overall Diameter:

0.781 inches

Environmental Protection:

Shock proof and vibration proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling nut

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.