## NSN 5935-00-835-4052

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-835-4052

**Body Style:** Straight edge type **Overall Length:** 6.188 inches **Overall Height:** 0.828 inches **Overall Width:** 0.594 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 5.938 inches **Board Accommodated Length:** 5.610 inches single board and 5.615 inches single board **Board Accommodated Width:** 0.074 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.0 single mating end single contact grouping **Polarization Method:** Inter-contact polarizing keys **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:** 

37 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

## NSN 5935-00-835-4052

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Polarizing pin located at position 5
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.037 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.037 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0