Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-835-7410

#### **Body Style:**

Straight shape, external coupling w/backshell

#### **Overall Length:**

1.359 inches

# **Overall Height:**

1.578 inches

# **Overall Width:**

1.578 inches

#### **Environmental Protection:**

Moisture proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

### Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

22-7 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Insert Material:**

Rubber single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping



**Shell Material:** Aluminum alloy Shell Surface Treatment: Cadmium and chromate **Included Contact Quantity:** 7 single mating end single contact grouping Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.007 gold grains, troy and 0.007 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0