Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-836-5284

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.621 inches	
Overall Height:	
Between 2.500 inches and 2.531 inches	
Overall Width:	
Between 2.500 inches and 2.531 inches	
Environmental Protection:	
Pressure proof and moisture resistant and vibration resistant	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.245 inches and 1.255 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width	า:
Between 1.245 inches and 1.255 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.750 inches and 0.781 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
22-14 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
22.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	



**Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromium **Included Contact Quantity:** 19 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0