NSN 5935-00-837-1341

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-837-1341

$\mathbf{R} \mathbf{a} \mathbf{d}$	w	Sty	٠ما
DOU	ı y	Oty	C.

Straight shape, external coupling w/backshell

Overall Length:

Between 1.146 inches and 1.186 inches

Overall Diameter:

Between 0.969 inches and 1.016 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

40515 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Conduit nut

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Shell Material Specification:

Qq-a-270, t-6 federal specification single material response

Insert Material Specification:

Mil-std-217 military specification single material response single mating end

NSN 5935-00-837-1341

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-217 spec.