Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-837-4652

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 3.190 inches and 3.210 inches

Overall Height:

Between 0.430 inches and 0.437 inches

Unthreaded Mounting Hole Diameter:

Between 0.245 inches and 0.255 inches

Distance Between Mounting Facility Centers:

Between 2.943 inches and 2.957 inches

Board Accommodated Length:

2.493 inches single board and 2.507 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.