NSN 5935-00-837-6084

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-837-6084

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape w/solder mount
Overall Length:
1.343 inches
Overall Diameter:
0.690 inches
Environmental Protection:
Moisture resistant
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Test Data Document:

81349-mil-prf-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5935-00-837-6084

Mil-std (military Standard):

Mil-prf-39012 spec.

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:	
Unef	
Specification Data:	
81349-mil-prf-39012/24 goverment specification government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	