NSN 5935-00-838-1903

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-838-1903

Bo	dy	,	St	yle:
_				

Straight edge type w/mounting flange

Overall Length:

4.597 inches

Overall Height:

0.660 inches

Overall Width:

0.343 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Board Accommodated Width:

0.082 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

NSN 5935-00-838-1903

Electrical Receptacle Connector - Page 2 of 2



Precious Material	And Weight:	
0.014 gold grains, t	roy and 0.024 silver grains,	troy
Precious Material:		
Gold and silver		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A039b0		

Mil-std (military Standard):

Mil-m-14 spec.