Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-838-6897

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
1.105 inches
Overall Diameter:
Between 1.796 inches and 1.828 inches
Environmental Protection:
Moisture resistant
Distance From Mounting Shoulder To Front Face:
Between 0.868 inches and 0.900 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.250 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
20-16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### Insert Material:

Rubber single mating end

### Terminal Type:

Solder well single mating end single contact grouping

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

16 single mating end single contact grouping

# Bushing Accommodation Hole Shape:

Round keyed

### Included Contact Type:

Round socket single mating end single contact grouping

### Precious Material And Location:

Contact surface gold and contact surface silver

### Precious Material And Weight:

 $0.016\ gold\ grains,\ troy\ and\ 0.016\ silver\ grains,\ troy$ 

Precious Material:

Gold and silver

#### Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A039b0