## NSN 5935-00-839-0726

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-839-0726
Body Style:
Single card
Overall Length:
2.406 inches
Overall Width:
0.531 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Distance Between Mounting Facility Centers:
2.134 inches
Board Accommodated Length:
1.815 inches single board
Board Accommodated Width:
0.074 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Nickel single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14f, ty sdgf military specification single material response single mating end

**Included Contact Quantity:** 

17 single mating end single contact grouping

## NSN 5935-00-839-0726

Electrical Receptacle Connector - Page 2 of 2



Spring pincers single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.017 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.