Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-840-0931

Thread Class:         2b         Thread Direction:         Laft-hand         Overall Length:         11.628 indees         Body Length:         Between 4.046 inches and 4.135 inches         Overall Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         1         Mounting Facility Type And Quantity:         1         I threaded coupling         Thread Size:         2.062 inches         Special Factures:         Wikellums cable relief grip         Matrial:         Aurninum altoy         Surface Treatment:         Cadmium         Strid poly type wistrin relief         Surface Treatment:         Cadmium         Thread Series Designator:         Na         Durit Of Measure:         ·         Durit Of Measure:         ·         Durit Of Measure:         ·         Durit Of Measure:         · <tr< th=""><th>Three</th><th></th></tr<>	Three	
Thread Direction:         Left-hand         Overall Length:         11.628 inches         Body Length:         Between 4.046 inches and 4.136 inches         Overall Diameter:         Between 2.092 Inches and 2.322 inches         Cable Opening Diameter:         0.967 inches         O 2097 Inches and 2.322 inches         Cable Opening Diameter:         0.967 inches         Cable Opening Diameter:         0.967 inches         Cable Opening Diameter:         0.967 inches         Cable Opening Diameter:         1         Monting Facility Type And Quantity:         1 threaded coupling         Thready Cay Per Inch (npi):         16         Thread Size:         2.062 inches         Super Teatment:         Mumium alloy         Surface Teatment:         Cadmiun         Stripty type wistrain relief         Surface Teatment:         Cadmiun         Thread Series Designator:         Stripty traite:         Na         Dirt of Messure:         Na         Dirt of Messure:         Na         Dirt of Mes		
Left-hand         Overall Length:         11.628 inches         Boly Length:         Between 4.045 inches and 4.135 inches         Overall Diameter:         Overall Diameter:         0.957 inches         Cable Opening Quantity:         1         Monting Facility Type And Quantity:         1         Monting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Special Features:         2.062 inches         Special Features:         Watelums cable relief grip         Material:         Auminum alloy         Surface Treatment:         Cadmium         Thread Streis Designator:         Infree Testing Designator:		
Overall Length:         11.628 inches         Body Length:         Between 4.045 inches and 4.135 inches         Overall Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1         1 threaded coupling         Thready Qip Per Inch (tpi):         16         Special Features:         2.062 inches         Special Features:         Vikellums cable relief grip         Material:         Aurinum alloy         Stradget type wistrain relief         Surface Treatment:         Cadmium         Thread Seles Designator:         Cardmium         Thread Seles Designator:         Narface Treatment:         Cadmium         Thread Seles Designator:         Narface Treatment:         Cadmium         Thread Seles Designator:         Narface Treatment:         Cadmium         Thread Seles Designator:         Narface Treatment:         Diafe Treatment:         Narface Treatment:		
11.628 inches         Between 4.045 inches and 4.135 inches         Dereil Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Threaded coupling         Threaded coupling         Threaded Size:         2.062 inches         Special Features:         Vikelums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Strafe Tosting Displator:         Cadmium         Strafe Treatment:         Cadmium         Thread Straip Logis Log		
Body Length:         Between 4.045 inches and 4.135 inches         Overall Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Special Features:         Vokeliums cable relief grip         Material:         Aurninum alloy         Syle Designator:         Cadmium         Strade Treatment:         Cadmium         Thread Series Designator:         Na         Strade Treatment:         Cadmium         Thread Series Designator:         Na         Strade Tr		
Between 4.045 inches and 4.135 inches         Overall Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1         Intreaded coupling         Thready Opy Per Inch (tpi):         16         Special Features:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Auminum alloy         Surface Treatment:         Cadmium         Straight type wistrain relief         Surface Treatment:         Cadmium         Finead Streis:         No         Surface Treatment:         Cadmium         Surface Treatment:         Cadmium         Surface Treatment:         Inter Surface Treatment:         Cadmium         Thread Surface Treatment:         Cadmium         Thread Surface Treatment:         Cadmium         Thread Surface Treatment:         Cadmium         Finitiarization:         Na <th></th> <th></th>		
Overall Diameter:         Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Pen And Quantity:         1 threaded coupling         Thready Qty Pen And Quantity:         1 threaded coupling         Water State         2.062 inches         Special Features:         2.062 inches         Special Features:         Vkellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Style posignator:         Straight type w/strain relief         Surface Treatment:         Cadmium         Thread Series Designator:         Unef         Surface Treatment:         Inef         Na         Infor Measure:         Infor M		
Between 2.092 inches and 2.322 inches         Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Style Designator:         Straight type wistrain relief         Surface Treatment:         Cadmium         Thread Series Designator:         Via         Na         Cadmium         Thread Series Designator:         Via         Na         Cadmium         Thread Series Designator:         Na         Unof         Shell Life:         Na         Cadmium         Thread Series Designator:         Na         Shell Life:         Na         Shell Life:         Na         Shell Mesure: <tr< th=""><th></th><th></th></tr<>		
Cable Opening Diameter:         0.957 inches         Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Vikellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmiun         Syle Designator:         Straight type w/strain relief         Durface Treatment:         Cadmiun         Straight type w/strain relief         Durface Treatment:         Cadmium         Straight type w/strain relief         Durface Treatment:         Cadmium         Thread Stries Designator:         Inter Stries Designator:         Inter Stries Designator:         Inter Stries Designator:         Na         Durface Treatment:         Inter Stries Designator:         Inter Stries Designator: <t< th=""><th></th><th></th></t<>		
0.957 inches Cable Opening Quantity: 1  Mounting Facility Type And Quantity: 1 Intreaded coupling Thready Qty Per Inch (tpl): 1 1  Thready Qty Per Inch (tpl): 1 1  Thread Size: 2.062 inches Special Features: 2.062 inc		
Cable Opening Quantity:         1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Aluminum alloy         Strafee Treatment:         Cadmium         Straight type w/strain relief         Surface Treatment:         Cadmium         Straight type w/strain relief         Surface Treatment:         Cadmium         Straight type w/strain relief         Surface Treatment:         Cadmium         Thread Series Designator:         Unef         Straight type w/strain relief         Surface Treatment:         Cadmium         Thread Series Designator:         Unef         Straight Life:         Na         Na         The Masure:         To         Straight Life:         Na         Straight Life:         Straight Life:         Straight Life:         Straight Life:		
1         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Aluminum alloy         Strigee Treatment:         Cadmium         Strige Treatment:         Cadmium         Thread Series Designator:         Unef         Strige Treatment:         Cadmium         Thread Series Designator:         Unef         Strige Treatment:         Cadmium         Thread Series Designator:         Inter of Measure:         T         Femilitarization:         No         Fig:		
Hounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wikellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Style Designator:         Straight type wistrain relief         Cadmium         Thread Series Designator:         Unef         Sheft Life:         Na         Thread Series Designator:         Unef         Sheft Life:         Na         Philitarization:         Formilitarization:         No         Fig:		e Opening Quantity.
1 thready cupling         Thready Cup Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Syle Designator:         Straight type w/strain relief         Cadmium         Thread Series Designator:         Unef         Shelf Life:         Na         Unef         Denilitarization:         No         Fig:		ating Easility Type And Ouentity
Thready Qty Per Inch (tpi):         16         Thread Size:         2.062 inches         Special Features:         Wikellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Style Designator:         Straight type w/strain relief         Dariace Treatment:         Cadmium         Pheread Series Designator:         Unef         Buef Infe:         Na         Unef         Duef Infe:         Na         Duef Infe:         Na         Duef Infe:         Na         Fiel Infe:         Na         Fiel Infe:         Na         Fiel Infe:         Na         Fiel Infe:         Na         Support Infer In		
16         Tread Size:         2.062 inches         Special Features:         Wkellums cable relief grip         Material:         Aluminum alloy         Surface Treatment:         Cadmium         Stright type w/strain relief         Surface Treatment:         Cadmium         Straight type w/strain relief         Burface Treatment:         Cadmium         Thread Series Designator:         Unef         Shelf Life:         Na         Fund Series Designator:         Inter Series Designator:         Na         Dunif         Na         Fig:		
Thread Size:2.062 inchesSpecial Features:Wkellums cable relief gripMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumStraight type and the straight stra		ady Qty Per Inch (tpi):
2.062 inches Special Features: W/kellums cable relief grip Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unif Of Measure: Fig: Double Sector Sec		
Special Features:W/kellums cable relief gripMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:NoFig:		
W/kellums cable relief gripMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnt Of Measure:-Demilitarization:NoFig:		
Material:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:		
Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:		
Surface Treatment:CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:		
CadmiumStyle Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:		-
Style Designator:Straight type w/strain reliefSurface Treatment:CadmiumThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:		
Straight type w/strain relief Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Cadmium         Thread Series Designator:         Unef         Shelf Life:         N/a         Unit Of Measure:            Penilitarization:         No         Fig:	-	
Thread Series Designator:   Unef   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:		
Unef Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:		
N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure:  Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		Of Measure:
No Fiig:	Unit	
No Fiig:	 Demi	ilitarization -
Fiig:		
		00
	AIUI	