NSN 5935-00-840-2829

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-840-2829 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.438 inches **Overall Height:** 2.250 inches **Overall Width:** 2.250 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.173 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.750 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 22.0 single mating end 3rd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 3rd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 4200.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-840-2829

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
8 single mating end 3rd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.