NSN 5935-00-840-3924

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-840-3924

Body Style:

Rectangular shape, insulation piercing

Overall Length:

2.685 inches

Overall Height:

0.704 inches

Overall Width:

0.610 inches

Environmental Protection:

Moisture resistant and thermal shock resistant

Distance Between Mounting Facility Centers:

2.352 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Astm-b-105, grade 95 assn standard single material response single mating end single contact grouping

Shell Material:

Copper alloy

NSN 5935-00-840-3924

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Material Specification:
Qq-b-626; composition 2 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.036 gold grains, troy and 0.036 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):