Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-840-4135

| Thread Direction:   |
|---|
| Right-hand  |
| Overall Height:   |
| 4.250 inches  |
| Body Length:  |
| 6.312 inches  |
| Body Width:   |
| 4.250 inches  |
| Environmental Protection:   |
| Weather resistant   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| 3.500 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 3.500 inches  |
| Threaded Device Type:   |
| Mounting stud   |
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Nonremovable single mating end all contact groupings                        |
| Contact Maximum Current Rating In Amps:                                     |
| 100.0 single mating end 2nd contact grouping                                |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 600.0 single mating end 2nd contact grouping                                |
| Contact Maximum Dc Voltage Rating In Volts:                                 |
| 250.0 single mating end 2nd contact grouping                                |
| Thready Qty Per Inch (tpi):   |
| 18  |
| Thread Size:  |
| 0.313 inches  |
| Insert Material:  |
| Plastic single mating end   |
| Shell Material:   |
| Steel   |
| Included Contact Quantity:  |
| 3 single mating end 2nd contact grouping                                    |
| Included Contact Type:  |
| Round socket single mating end all contact groupings                        |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
|   |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0