Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-841-4980

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 0.510 inches |
| Overall Diameter: |
| 0.250 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.283 inches |
| Mounting Facility Thickness: |
| 0.210 inches |
| Threaded Device Type: |
| Coupling facility and mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 0.190 inches and 0.190 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic tetrafluoroethylene single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round w/double flat |



Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf and unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0