
NSN 5935-00-842-2166

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Orange **Body Style:** Threaded bushing mounted **Overall Length:** 0.938 inches Mounting Bushing Length: 0.469 inches **Body Length:** 0.657 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 12500.0 dc Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.175 inches single finger Finger Accommodation Length: 0.657 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.313 inches **Capacitance In Picofarads:** 2.4 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Terminal Type:** Tab, solder lug Material: Plastic cap

NSN 5935-00-842-2166

Tip Jack - Page 2 of 2

Material: Plastic cap Surface Treatment: Nickel spring Surface Treatment: Nickel spring **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: Demilitarization:

No Fiig:

A03400

