

View Online at <https://aerobasegroup.com/nsn/5935-00-843-1271>

Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

Between 1.094 inches and 1.141 inches

Body Angle In Deg:

90.0

Mating End Quantity:

1

Contact Position Arrangement Style:

18-28 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

5000.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

6000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Qq-a-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Ams 9610 assn standard single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-f-14072, finish e516 military specification single treatment response

Shell Material Specification:

Qq-a-367c, comp 3 0r comp 11, qq-a-270 federal specification single material response

Insert Material Specification:

Mil-r-3065, class sc 717a, b, e or f military specification single material response single mating end

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.