NSN 5935-00-844-3143

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-844-3143

2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.062 inches
Overall Diameter:
0.688 inches
Environmental Protection:
Watertight
Distance From Mounting Shoulder To Front Face:
0.672 inches
Mounting Facility Thickness:
0.135 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Gold single mating end single contact grouping and silver single mating end single contact grouping

Contact Surface Treatment:

NSN 5935-00-844-3143

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Furnished items - boot
Precious Material And Location:
Contact surface gold and contact surface and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.105 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0