Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-844-4142

# Body Style:

Straight shape, external coupling

#### **Overall Length:**

1.076 inches

# **Overall Height:**

Between 1.546 inches and 1.578 inches

#### **Overall Width:**

Between 1.546 inches and 1.578 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 1.250 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

#### Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.566 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

22-55 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

226.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

# **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# NSN 5935-00-844-4142

Electrical Receptacle Connector - Page 2 of 2

