## NSN 5935-00-844-6498

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-844-6498



2a **Thread Direction:** Right-hand **Body Style:** Thru-hole mount **Overall Length:** 0.750 inches **Bushing Diameter:** 0.500 inches **Overall Diameter:** 0.780 inches **Distance From Mounting Shoulder To Rear Face:** 0.300 inches **Mounting Facility Thickness:** 0.210 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Mh-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Latch Thready Qty Per Inch (tpi): **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-m-19833, ty gdi-30 military specification single material response single mating end

## NSN 5935-00-844-6498

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Mtg. Bushing nut not supplied
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-19833 spec.