

basegroup.com/nsn/5935-00-844-9376

View Online at https://aerobasegroup.com/nsn/5935-00-84Thread Class:2a and 2bThread Direction:Right-hand and right-handBody Style:Hood, top opening w/clampOverall Length:1.312 inchesOverall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:11Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:1.3.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top openingConnector Locking Method:	NSN 5935-00-844-9376 Electrical Plug Connector - Page 1 of 2
2a and 2b Thread Direction: Right-hand and right-hand Body Style: Hood, top opening w/clamp Overall Length: 1.312 inches Overall Height: 2.094 inches Overall Width: 0.438 inches Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	View Online at https://aerobasegroup.com/nsn/5935-00-8-
Thread Direction:Right-hand and right-handBody Style:Hood, top opening w/clampOverall Length:1.312 inchesOverall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Thread Class:
Right-hand and right-handBody Style:Hood, top opening w/clampOverall Length:1.312 inchesOverall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	2a and 2b
Body Style:Hood, top opening w/clampOverall Length:1.312 inchesOverall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Thread Direction:
 Hood, top opening w/clamp Overall Length: 1.312 inches Overall Height: 2.094 inches Overall Width: 0.438 inches Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: Single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	Right-hand and right-hand
Overall Length:1.312 inchesOverall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact grouping13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Body Style:
 1.312 inches Overall Height: 2.094 inches Overall Width: 0.438 inches Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	Hood, top opening w/clamp
Overall Height:2.094 inchesOverall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Overall Length:
 2.094 inches Overall Width: 0.438 inches Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	1.312 inches
Overall Width:0.438 inchesCable Entrance Diameter:0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Overall Height:
 0.438 inches Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	2.094 inches
Cable Entrance Diameter: 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Overall Width:
 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	0.438 inches
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Cable Entrance Diameter:
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	0.312 inches
Mating End Quantity:1Contact Position Arrangement Style:9 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:Hood, top opening	Threaded Device Type:
1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Coupling facility
Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Mating End Quantity:
 9 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	1
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Contact Position Arrangement Style:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	9 single mating end
Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening	Contact Removability:
 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Hood, top opening 	Nonremovable single mating end single contact grouping
Polarization Method: Jackscrew Shell Type: Hood, top opening	Contact Maximum Current Rating In Amps:
Jackscrew Shell Type: Hood, top opening	13.0 single mating end single contact grouping
Shell Type: Hood, top opening	Polarization Method:
Hood, top opening	Jackscrew
	Shell Type:
Connector Locking Method:	Hood, top opening
	Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Size:

0.138 inches and 0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Paper single mating end

NSN 5935-00-844-9376

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0