NSN 5935-00-845-4481

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-845-4481 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.209 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-8 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-845-4481

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
16
Thread Size:
2.250 inches
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Rubber chloroprene class cr single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, graded b military specification 1st treatment response single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
46 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.