Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-845-6831

Intread Utass: 2a Thread Direction: Right-hand Body Style: Straight shape, external coupling Overall Weight: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between 0.967 inches and 0.977 inches Distance Form Mounting Shoulder To Front Face: Between 0.967 inches and 0.977 inches Distance Form Mounting Shoulder To Front Face: Between 0.452 inches and 0.454 inches Threaded Device Type: Couping facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end single contact grouping Contact Removability: Normerovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Contact Loching Method: Externally threaded shell <th>Thread Class:</th>	Thread Class:
Tread Direction: Right-hand Body Style: Straight shape, external coupling Overall Height: Between 1.296 inches and 1.328 inches Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Studier To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Meximum Current Rating In Amps: 15.0 single mating end single contact grouping Polization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Oly Per Inch (tpi): 6	
Right-hand Body Style: Straight shape, external coupling Overall Height: Between 1.296 inches and 1.328 inches Outraded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Schulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Vk-3 single mating end single contact grouping Contact Menovability: Nonremovable single mating end single contact grouping Polization Method: Keyway or multiple keyway Insert Position In Deg: Soid Contact Cocking Method: Soid Contact Cocking Method: Reservery or multiple keyway Insert Position In Deg: Soid Connector Locking Method:	
Body Style: Straight shape, external coupling Overall Height: Between 1.296 inches and 1.328 inches Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end single contact grouping Contact Removability: Nornerovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Contact Chring Method: Externally threaded shell Thready Clype Inch (tpi): 6 <	
Straight shape, external coupling Overall Height: Between 1.296 inches and 1.328 inches Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Souries mound and single contact grouping Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Soid Conctor Locking Method: Externally threaded shell Thready Gyper Inch (tpi): 6	
Overall Height: Between 1.296 inches and 1.328 inches Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end single contact grouping Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Sold Connector Locking Method: Externally threaded shell Thread Quip Per Inch (tpi): 6 Thread Size: 0.875 inches	
Between 1.296 inches and 1.328 inches Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Soling mating end Contact Removability: Norremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: Solid Contact Locking Method: Externally threaded shell Thready Gty Per Inch (tp): 6 Thread Size: 0.875 inches	
Overall Width: Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shild Connect Locking Method: Externally threaded shell Threaded Juper Inch (tpi): 6 Thread Size: 0.875 inches	-
Between 1.296 inches and 1.328 inches Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches	
Unthreaded Mounting Hole Diameter: Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Torinal Location:	
Between 0.139 inches and 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Thread Size:	
Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Vk-3 single mating end Mk-3 single mating end Solid Contact Removability: Nonremovable single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches	-
Between 0.967 inches and 0.977 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Reyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Gty Per Inch (tpi): 6 Thread Size: 0.875 inches Cincetion:	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Reyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Carrinal Location:	
Between 0.967 inches and 0.977 inches Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	
Distance From Mounting Shoulder To Front Face: Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	
Between 0.422 inches and 0.454 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Carter Size: 0.875 inches	-
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Contact Size:	
Mating End Quantity: 1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	
1 Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	
Contact Position Arrangement Style: Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches	
Wk-3 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Contact Position Arrangement Style:
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:15.0 single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):6Thread Size:0.875 inchesTerminal Location:	
Contact Maximum Current Rating In Amps: 15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Contact Removability:
15.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Nonremovable single mating end single contact grouping
Polarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):6Thread Size:0.875 inchesTerminal Location:	Contact Maximum Current Rating In Amps:
Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):6Thread Size:0.875 inchesTerminal Location:	15.0 single mating end single contact grouping
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Polarization Method:
0.0 Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Keyway or multiple keyway
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):6Thread Size:0.875 inchesTerminal Location:	Insert Position In Deg:
Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	0.0
Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Shell Type:
Externally threaded shell Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Solid
Thready Qty Per Inch (tpi): 6 Thread Size: 0.875 inches Terminal Location:	Connector Locking Method:
6 Thread Size: 0.875 inches Terminal Location:	Externally threaded shell
Thread Size: 0.875 inches Terminal Location:	Thready Qty Per Inch (tpi):
0.875 inches Terminal Location:	6
Terminal Location:	Thread Size:
	0.875 inches
Back single mating end single contact grouping	Terminal Location:
	Back single mating end single contact grouping



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping or silver single mating end single contact grouping **Insert Material:** Plastic melamine single mating end or plastic phenolic single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.003 gold grains, troy and 0.003 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0