## NSN 5935-00-845-9594

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-845-9594 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape **Overall Length:** 2.250 inches **Overall Height:** 0.797 inches **Overall Width:** 0.375 inches **Distance Between Mounting Facility Centers:** 1.937 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 21 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Length:** 0.266 inches Thready Qty Per Inch (tpi): 32 and 40 **Thread Size:** 0.138 inches and 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic polytetrafluoroethylene single mating end

## NSN 5935-00-845-9594

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.021 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0