NSN 5935-00-846-2727



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-846-2727 **Thread Class:** 2a **Thread Pitch Diameters:** +1.179/+1.188 inches **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 1.250 inches **Overall Height:** 1.250 inches **Overall Width:** 1.250 inches **Environmental Protection:** Salt water resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.972 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.972 inches **Distance From Mounting Shoulder To Front Face:** 0.375 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 19-20 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 2400.0 single mating end 1st contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end 2nd contact grouping **Polarization Method:**

Polarization Method

Keyway or multiple keyway

Insert Position In Deg:

80.0

NSN 5935-00-846-2727

A039b0

Electrical Receptacle Connector - Page 2 of 2



| Shall Type: |
|---|
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thready Qty Per Inch (tpi): |
| 6 |
| Thread Size: |
| 1.188 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings and silver single mating end all contact groupings |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Crimp single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 3 single mating end 1st contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Special acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |