## NSN 5935-00-846-5444

Aluminum alloy

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-846-5444

| Body Style:   |
|---|
| Straight shape, internal coupling w/strain relief   |
| Body Length:  |
| 1.870 inches  |
| Overall Diameter:   |
| 1.082 inches  |
| Environmental Protection:   |
| Vibration resistant   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 14-12 single mating end   |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Contact Maximum Ac Voltage Rating In Volts:   |
| 500.0 single mating end single contact grouping   |
| Contact Maximum Dc Voltage Rating In Volts:   |
| 700.0 single mating end single contact grouping   |
| Polarization Method:  |
| Key, multiple key groove  |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Spring friction   |
| Connector Cable Strain Relief Method:   |
| Cable clamp   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material:  |
| Plastic diallyl phthalate single mating end   |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |

## NSN 5935-00-846-5444

Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Anodize  |
| Shell Surface Treatment Specification:                                     |
| Mil-a-8625 military specification single treatment response                |
| Insert Material Specification:   |
| Mil-m-14 military specification single material response single mating end |
| Included Contact Quantity:   |
| 12 single mating end single contact grouping                               |
| Included Contact Type:   |
| Round pin single mating end single contact grouping                        |
| Precious Material And Location:  |
| Contact surfaces gold and contact surfaces silver                          |
| Precious Material And Weight:  |
| 0.012 gold grains, troy and 0.012 silver grains, troy                      |
| Precious Material:   |
| Gold and silver  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |

Mil-m-14 spec.