

View Online at <https://aerobasegroup.com/nsn/5935-00-846-8204>

Body Style:

Straight shape, internal coupling

Overall Length:

1.803 inches

Overall Diameter:

0.575 inches

Cable Entrance Diameter:

0.242 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

5000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

50.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Crimp type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Weatherproof

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.001 gold grains, troy and 0.001 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0