

View Online at <https://aerobasegroup.com/nsn/5935-00-847-1316>

Body Style:

Straight shape, internal coupling

Overall Length:

1.343 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Moisture resistant and vibration resistant

Cable Entrance Diameter:

0.155 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

750.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Snap ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

95.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Silver single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Material Specification:

Mil-s-13282, grade c, hard temper military specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact body materiel and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 1.100 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-s-13282 spec.