Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-847-1666

Body Style:
Straight shape
Overall Length:
Between 3.321 inches and 3.371 inches
Overall Height:
Between 0.610 inches and 0.672 inches
Overall Width:
Between 0.578 inches and 0.608 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
3.000 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end



Included Contact Quantity: 14 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Polarized p contact removed **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.