Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-847-1670

- **Body Style:** Straight shape **Overall Length:** 3.844 inches **Overall Height:** 0.641 inches **Overall Width:** 0.438 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.139 inches and 0.149 inches **Distance Between Mounting Facility Centers:** Between 3.428 inches and 3.488 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Turret single mating end single contact grouping **Contact Material Specification:** Qq-b-530, comp a federal specification single material response single mating end single contact grouping **Shell Material:**
- Aluminum alloy

NSN 5935-00-847-1670

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Anodize **Shell Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Insert Material Specification:** Mil-m-14, ty mdg military specification single material response single mating end **Included Contact Quantity:** 15 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Polarized contact m **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.

No