

View Online at <https://aerobasegroup.com/nsn/5935-00-847-1676>

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.410 inches

Overall Height:

0.458 inches

Overall Width:

0.340 inches

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

2.156 inches

Board Accommodated Length:

1.723 inches single board

Board Accommodated Width:

0.088 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-14548, type 1 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Special Features:

Polarized key located position e

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-14548 spec.