# NSN 5935-00-847-6193

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-847-6193

### Body Style:

Angle shape w/cable clamp

### **Overall Diameter:**

1.297 inches

# Body Angle In Deg:

90.0

### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

### Cable Entrance Diameter:

0.330 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

16-26 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Cable End:

1.030 inches

Terminal Location:

Back single mating end single contact grouping

# Contact Material:

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# Insert Material:

Rubber single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping

# NSN 5935-00-847-6193

Electrical Plug Connector - Page 2 of 2



**Shell Surface Treatment:** Anodize Included Contact Quantity: 26 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.026 gold grains, troy and 0.026 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0