NSN 5935-00-847-7297

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-847-7297 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.344 inches **Overall Diameter:** Between 1.990 inches and 2.010 inches **Environmental Protection:** Explosion proof and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 1.146 inches and 1.166 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.250 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-22 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 46.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi):

10 and 10

Thread Size:

1.375 inches and 1.375 inches

NSN 5935-00-847-7297

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.020 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0