Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-848-6435

Thread Class:
2g
Thread Pitch Diameters:
+2.000/+2.011 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
2.703 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
0.195 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.687 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.687 inches
Distance From Mounting Shoulder To Front Face:
1.005 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-345 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
73.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway

Electrical Receptacle Connector - Page 2 of 3



Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

1.005 inches

Thready Qty Per Inch (tpi):

8

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - protective cover and link chain

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5935-00-848-6435

Electrical Receptacle Connector - Page 3 of 3

Fiig: A039b0

